

Package: JDCruncheR (via r-universe)

September 6, 2024

Type Package

Title Interface Between the 'JDemetra+' Cruncher and R, and Quality Report Generator

Version 0.2.4

Description Tool for generating quality reports from cruncher outputs (and calculating series scores). The latest version of the cruncher can be downloaded here:
<<https://github.com/jdemetra/jwsacruncher/releases>>.

URL <https://github.com/InseeFr/JDCruncheR>,
<https://insee.fr.github.io/JDCruncheR/>

BugReports <https://github.com/InseeFr/JDCruncheR/issues>

Imports openxlsx, stats, utils

Suggests knitr, kableExtra, pkgdown, rmarkdown

License EUPL

VignetteBuilder knitr

Encoding UTF-8

LazyData true

RoxygenNote 7.3.2

Roxygen list(markdown = TRUE)

Repository <https://tanguybarthelemy.r-universe.dev>

RemoteUrl <https://github.com/InseeFr/JDCruncheR>

RemoteRef HEAD

RemoteSha 5763c6a1017b3510aa3d61024cbd1f57a4426f52

Contents

add_indicator	2
compute_score	3
export_xlsx	5

export_xlsx.mQR_matrix	6
export_xlsx.QR_matrix	7
extract_QR	7
extract_score	9
print.QR_matrix	10
QR_matrix	11
QR_var_manipulation	12
rbind.QR_matrix	13
recode_indicator_num	14
sort	15
weighted_score	16

Index	18
--------------	-----------

add_indicator	<i>Adding an indicator in QR_matrix objects</i>
---------------	---

Description

Function to add indicators in `QR_matrix` objects.

Usage

```
add_indicator(x, indicator, variable_name, ...)
```

Arguments

<code>x</code>	a <code>QR_matrix</code> or <code>mQR_matrix</code> object
<code>indicator</code>	a vector or a <code>data.frame</code> (cf. details).
<code>variable_name</code>	a string containing the name of the variables to add.
<code>...</code>	other parameters of the function <code>merge</code> .

Details

The function `add_indicator()` adds the chosen indicator to the values matrix of a quality report. Therefore, because said indicator isn't added in the modalities matrix, it cannot be used to calculate a score (except for weighting). Before using the added variable for score calculation, it will have to be coded with the function `recode_indicator_num`.

The new indicator can be a vector or a `data.frame`. In both cases, its format must allow for pairing:

- a vector's elements must be named and these names must match those of the quality report (variable "series");
- a `data.frame` must contain a "series" column that matches with the quality report's series.

Value

This function returns the same object, enhanced with the chosen indicator. So if the input `x` is a `QR_matrix`, an object of class `QR_matrix` is returned. If the input `x` is a `mQR_matrix`, an object of class `mQR_matrix` is returned.

See Also

[Traduction française](#)

Other var `QR_matrix` manipulation: [QR_var_manipulation](#), [recode_indicator_num\(\)](#)

compute_score	<i>Score calculation</i>
---------------	--------------------------

Description

To calculate a score for each series from a quality report

Usage

```
## S3 method for class 'QR_matrix'
compute_score(
  x,
  score_pond = c(qs_residual_sa_on_sa = 30, f_residual_sa_on_sa = 30, qs_residual_sa_on_i
    = 20, f_residual_sa_on_i = 20, f_residual_td_on_sa = 30, f_residual_td_on_i = 20,
    oos_mean = 15, oos_mse = 10, residuals_independency = 15, residuals_homoskedasticity
    = 5, residuals_skewness = 5, m7 = 5, q_m2 = 5),
  modalities = c("Good", "Uncertain", "", "Bad", "Severe"),
  normalize_score_value,
  na.rm = FALSE,
  n_contrib_score,
  conditional_indicator,
  ...
)
```

Arguments

<code>x</code>	a <code>QR_matrix</code> or <code>mQR_matrix</code> object.
<code>score_pond</code>	the formula used to calculate the series score.
<code>modalities</code>	modalities ordered by importance in the score calculation (cf. details).
<code>normalize_score_value</code>	integer indicating the reference value for weights normalisation. If missing, weights will not be normalised.
<code>na.rm</code>	logical indicating whether missing values must be ignored when calculating the score.

n_contrib_score	integer indicating the number of variables to create in the quality report's values matrix to store the n_contrib_score greatest contributions to the score (cf. details). If not specified, no variable is created.
conditional_indicator	a list containing 3-elements sub-lists: "indicator", "conditions" and "conditions_modalities". To reduce down to 1 the weight of chosen indicators depending on other variables' values (cf. details).
...	other unused parameters.

Details

The function `compute_score` calculates a score from the modalities of a quality report: to each modality corresponds a weight that depends on the parameter `modalities`. The default parameter is `c("Good", "Uncertain", "Bad", "Severe")`, and the associated weights are respectively 0, 1, 2 and 3.

The score calculation is based on the `score_pond` parameter, which is a named integer vector containing the weights to apply to the (modalities matrix) variables. For example, with `score_pond = c(qs_residual_sa_on_sa = 10, f_residual_td_on_sa = 5)`, the score will be based on the variables `qs_residual_sa_on_sa` and `f_residual_td_on_sa`. The `qs_residual_sa_on_sa` grades will be multiplied by 10 and the `f_residual_td_on_sa` grades, by 5. To ignore the missing values when calculating a score, use the parameter `na.rm = TRUE`.

The parameter `normalize_score_value` can be used to normalise the scores. For example, to have all scores between 0 and 20, specify `normalize_score_value = 20`.

When using parameter `n_contrib_score`, `n_contrib_score` new variables are added to the quality report's values matrix. These new variables store the names of the variables that contribute the most to the series score. For example, `n_contrib_score = 3` will add to the values matrix the three variables that contribute the most to the score. The new variables' names are `i_highest_score`, with `i` being the rank in terms of contribution to the score (`1_highest_score` contains the name of the greatest contributor, `2_highest_score` the second greatest, etc). Only the variables that have a non-zero contribution to the score are taken into account: if a series score is 0, all `i_highest_score` variables will be empty. And if a series score is positive only because of the `m7` statistic, `1_highest_score` will have a value of "m7" for this series and the other `i_highest_score` will be empty.

Some indicators are only relevant under certain conditions. For example, the homoscedasticity test is only valid when the residuals are independant, and the normality tests, only when the residuals are both independant and homoscedastic. In these cases, the parameter `conditional_indicator` can be of use since it reduces the weight of some variables down to 1 when some conditions are met. `conditional_indicator` is a list of 3-elements sub-lists:

- "indicator": the variable whose weight will be conditionally changed
- "conditions": the variables used to define the conditions
- "conditions_modalities": modalities that must be verified to induce the weight change For example, `conditional_indicator = list(list(indicator = "residuals_skewness", conditions = c("residuals_independency", "residuals_homoskedasticity"), conditions_modalities = c("Bad", "Severe")))`, reduces down to 1 the weight of the variable "residuals_skewness" when the modalities of the independancy test ("residuals_independency") or the homoscedasticity test ("residuals_homoskedasticity") are "Bad" or "Severe".

Value

a `QR_matrix` or `mQR_matrix` object.

See Also

[Traduction française](#)

Examples

```
# Path of matrix demetra_m
demetra_path <- file.path(
  system.file("extdata", package = "JDCruncheR"),
  "WS/ws_ipi/Output/SAProcessing-1",
  "demetra_m.csv"
)

# Extract the quality report from the demetra_m file
QR <- extract_QR(demetra_path)

# Calculer le score
QR <- compute_score(QR, n_contrib_score = 2)
print(QR)

# Extract the modalities matrix:
QR$modalities$score
```

export_xlsx

Exporting QR_matrix or mQR_matrix objects in an Excel file

Description

Exporting `QR_matrix` or `mQR_matrix` objects in an Excel file

Usage

```
export_xlsx(x, ...)
```

Arguments

`x` a `QR_matrix` or `mQR_matrix` object.
`...` other parameters of the function `export_xlsx.QR_matrix`.

Value

If `x` is a `mQR_matrix`, the function returns invisibly (via `invisible(x)`) the same `mQR_matrix` object as `x`. Else if `x` is a `QR_matrix`, the function returns invisibly (via `invisible(x)`) a workbook object created by `XLConnect::loadWorkbook()` for further manipulation.

See Also

Other QR_matrix functions: [export_xlsx.QR_matrix\(\)](#), [export_xlsx.mQR_matrix\(\)](#), [extract_QR\(\)](#), [rbind.QR_matrix\(\)](#), [sort\(\)](#), [weighted_score\(\)](#)

export_xlsx.mQR_matrix

Exporting mQR_matrix objects in Excel files

Description

To export several quality reports in Excel files

Usage

```
## S3 method for class 'mQR_matrix'
export_xlsx(
  x,
  export_dir,
  layout_file = c("ByComponent", "ByQRMatrix", "AllTogether"),
  auto_format = TRUE,
  overwrite = TRUE,
  ...
)
```

Arguments

x	a mQR_matrix object to export.
export_dir	export directory.
layout_file	export parameter. By default, (layout_file = "ByComponent") and an Excel file is exported for each part of the quality report matrix (modalities and values matrices). To group both modalities and values reports/sheets into a single Excel file, use the option layout_file = "ByQRMatrix".
auto_format	logical indicating whether to format the output (auto_format = TRUE by default).
overwrite	logical indicating whether to create an Excel file if it doesn't exist yet (create = TRUE by default)
...	other unused arguments

Value

Returns invisibly (via `invisible(x)`) the same [mQR_matrix](#) object as x.

See Also

[Traduction française](#)

Other QR_matrix functions: [export_xlsx\(\)](#), [export_xlsx.QR_matrix\(\)](#), [extract_QR\(\)](#), [rbind.QR_matrix\(\)](#), [sort\(\)](#), [weighted_score\(\)](#)

export_xlsx.QR_matrix *Exporting QR_matrix objects in an Excel file*

Description

To export a quality report in an Excel file.

Usage

```
## S3 method for class 'QR_matrix'
export_xlsx(x, file, auto_format = TRUE, overwrite = TRUE, ...)
```

Arguments

x	a QR_matrix object.
file	a character object with the path to the file to export que l'on veut créer
auto_format	logical indicating whether to format the output (auto_format = TRUE by default).
overwrite	logical indicating whether to create an Excel file if it doesn't exist yet (create = TRUE by default)
...	other unused arguments

Value

Returns invisibly (via `invisible(x)`) a workbook object created by `XLConnect::loadWorkbook()` for further manipulation.

See Also

[Traduction française](#)

Other `QR_matrix` functions: [export_xlsx\(\)](#), [export_xlsx.mQR_matrix\(\)](#), [extract_QR\(\)](#), [rbind.QR_matrix\(\)](#), [sort\(\)](#), [weighted_score\(\)](#)

extract_QR *Extraction of a quality report*

Description

To extract a quality report from the csv file containing the diagnostics matrix.

Usage

```
extract_QR(matrix_output_file, sep = ";", dec = ",")
```

Arguments

<code>matrix_output_file</code>	the csv file containing the diagnostics matrix.
<code>sep</code>	the separator used in the csv file (by default, <code>sep = ";"</code>)
<code>dec</code>	the decimal separator used in the csv file (by default, <code>dec = ","</code>)

Details

This function generates a quality report from a csv file containing diagnostics (usually from the file *demetra_m.csv*). The *demetra_m.csv* file can be generated by launching the cruncher (functions [cruncher](#) or [cruncher_and_param](#)) with the default export parameters, having used the default option `csv_layout = "vtable"` to format the output tables of the functions [cruncher_and_param](#) and [create_param_file](#) when creating the parameters file.

This function returns a [QR_matrix](#) object, which is a list of 3 objects:

- `modalities`, a `data.frame` containing several indicators and their categorical quality (Good, Uncertain, Bad, Severe).
- `values`, a `data.frame` containing the same indicators and the values that lead to their quality category (i.e.: p-values, statistics, etc.) as well as additional variables that don't have a modality/quality (series frequency and arima model).
- `score_formula` that will store the formula used to calculate the score (when relevant). Its initial value is `NULL`.

Value

a [QR_matrix](#) object.

See Also

[Traduction française](#)

Other [QR_matrix](#) functions: [export_xlsx\(\)](#), [export_xlsx.QR_matrix\(\)](#), [export_xlsx.mQR_matrix\(\)](#), [rbind.QR_matrix\(\)](#), [sort\(\)](#), [weighted_score\(\)](#)

Examples

```
# Path of matrix demetra_m
demetra_path <- file.path(
  system.file("extdata", package = "JDCruncher"),
  "WS/ws_ipi/Output/SAProcessing-1",
  "demetra_m.csv"
)

# Extract the quality report from the demetra_m file
QR <- extract_QR(demetra_path)

print(QR)

# Extract the modalities matrix:
```

```
QR$modalities
# Or:
QR[["modalities"]]
```

extract_score	<i>Score extraction</i>
---------------	-------------------------

Description

To extract score variables from [QR_matrix](#) or [mQR_matrix](#) objects.

Usage

```
extract_score(
  x,
  format_output = c("data.frame", "vector"),
  weighted_score = FALSE
)
```

Arguments

x a [QR_matrix](#) or [mQR_matrix](#).

format_output string of characters indicating the output format: either a `data.frame` or a vector.

weighted_score logical indicating whether to extract the weighted score (if previously calculated) or the unweighted one. By default, the unweighted score is extracted.

Details

For [QR_matrix](#) objects, the output is a vector or the object `NULL` if no score was previously calculated. For [mQR_matrix](#) objects, it is a list of scores (`NULL` elements or vectors).

Value

`extract_score()` returns a `data.frame` with two column: the series name and their score.

See Also

[Traduction française](#)

Examples

```

# Path of matrix demetra_m
demetra_path <- file.path(
  system.file("extdata", package = "JDCruncheR"),
  "WS/ws_ipi/Output/SAPProcessing-1",
  "demetra_m.csv"
)

# Extract the quality report from the demetra_m file
QR <- extract_QR(demetra_path)

# Compute the score
QR1 <- compute_score(x = QR, n_contrib_score = 5)
QR2 <- compute_score(
  x = QR,
  score_pond = c(qs_residual_sa_on_sa = 5, qs_residual_sa_on_i = 30,
                 f_residual_td_on_sa = 10, f_residual_td_on_i = 40,
                 oos_mean = 30, residuals_skewness = 15, m7 = 25)
)
mQR <- mQR_matrix(list(a = QR1, b = QR2))

# Extract score
extract_score(QR1)
extract_score(mQR)

```

print.QR_matrix *Printing QR_matrix and mQR_matrix objects*

Description

To print information on a QR_matrix or mQR_matrix object.

Usage

```

## S3 method for class 'QR_matrix'
print(x, print_variables = TRUE, print_score_formula = TRUE, ...)

## S3 method for class 'mQR_matrix'
print(x, score_statistics = TRUE, ...)

```

Arguments

x a `mQR_matrix` or `QR_matrix` object.

print_variables logical indicating whether to print the indicators' name (including additional variables).

`print_score_formula`
 logical indicating whether to print the formula with which the score was calculated (when calculated).
`...` other unused arguments.
`score_statistics`
 logical indicating whether to print the statistics in the `mQR_matrix` scores (when calculated).

Value

the `print` method prints a `mQR_matrix` or `QR_matrix` object and returns it invisibly (via `invisible(x)`).

See Also

[Traduction française](#)

QR_matrix *Quality report objects*

Description

`mQR_matrix()` and `QR_matrix()` are creating one (or several) quality report. The function `is.QR_matrix()` and `is.mQR_matrix()` are functions to test whether an object is a quality report or a list of quality reports.

Usage

```
QR_matrix(modalities = NULL, values = NULL, score_formula = NULL)
```

```
mQR_matrix(x = list(), ...)
```

```
is.QR_matrix(x)
```

```
is.mQR_matrix(x)
```

Arguments

`modalities` a `data.frame` containing the output variables' modalities (Good, Bad, etc.)
`values` a `data.frame` containing the output variables' values (test p-values, test statistics, etc.) Therefore, the values data frame can contain more variables than the data frame modalities.
`score_formula` the formula used to calculate the series score (if defined).
`x` a `QR_matrix` object, a `mQR_matrix` object or a list of `QR_matrix` objects.
`...` objects of the same type as `x`.

Details

AQR_matrix object is a list of three items:

- modalities, a data.frame containing a set of categorical variables (by default: Good, Uncertain, Bad, Severe).
- values, a data.frame containing the values corresponding to the modalities indicators (i.e. p-values, statistics, etc.), as well as variables for which a modality cannot be defined (e.g. the series frequency, the ARIMA model, etc).
- score_formula contains the formula used to calculate the series score (once the calculus is done).

Value

QR_matrix() creates and returns a QR_matrix object. mQR_matrix() creates and returns a mQR_matrix object (ie. a list of QR_matrix objects). is.QR_matrix() and is.mQR_matrix() return Boolean values (TRUE or FALSE).

See Also

[Traduction française](#)

QR_var_manipulation *Editing the indicators list*

Description

Functions to remove indicators (remove_indicators()) or retain some indicators only (retain_indicators()) from QR_matrix or mQR_matrix objects. The series names (column "series") cannot be removed.

Usage

```
remove_indicators(x, ...)
```

```
retain_indicators(x, ...)
```

Arguments

x	a QR_matrix or mQR_matrix object.
...	names of the variable to remove (or keep)

Value

remove_indicators() returns the same object x reduced by the flags and variables used as arguments ... So if the input x is a QR_matrix, an object of class QR_matrix is returned. If the input x is a mQR_matrix, an object of class mQR_matrix is returned.

See Also[Traduction française](#)Other var QR_matrix manipulation: [add_indicator\(\)](#), [recode_indicator_num\(\)](#)**Examples**

```

# Path of matrix demetra_m
demetra_path <- file.path(
  system.file("extdata", package = "JDCruncheR"),
  "WS/ws_ipi/Output/SAProcessing-1",
  "demetra_m.csv"
)

# Extract the quality report from the demetra_m file
QR <- extract_QR(demetra_path)

# Compute the score
QR <- compute_score(QR, n_contrib_score = 2)

# Retain indicators
retain_indicators(QR, "score", "m7") # retaining "score" and "m7"
retain_indicators(QR, c("score", "m7")) # Same

# Remove indicators
QR <- remove_indicators(QR, "score") # removing "score"

extract_score(QR) # is NULL because we removed the score indicator

```

rbind.QR_matrix

*Combining QR_matrix objects***Description**

Function to combine multiple [QR_matrix](#) objects: line by line, both for the modalities and the values table.

Usage

```

## S3 method for class 'QR_matrix'
rbind(..., check_formula = TRUE)

```

Arguments

... [QR_matrix](#) objects to combine.

check_formula logical indicating whether to check the score formulas' coherency. By default, check_formula = TRUE: an error is returned if the scores were calculated with different formulas. If check_formula = FALSE, no check is performed and the score_formula of the output is NULL.

Value

`rbind.QR_matrix()` returns a `QR_matrix` object.

See Also

[Traduction française](#)

Other `QR_matrix` functions: [export_xlsx\(\)](#), [export_xlsx.QR_matrix\(\)](#), [export_xlsx.mQR_matrix\(\)](#), [extract_QR\(\)](#), [sort\(\)](#), [weighted_score\(\)](#)

Examples

```
# Path of matrix demetra_m
demetra_path <- file.path(
  system.file("extdata", package = "JDCruncheR"),
  "WS/ws_ipi/Output/SAProcessing-1",
  "demetra_m.csv"
)

# Extract the quality report from the demetra_m file
QR <- extract_QR(demetra_path)

# Compute differents scores
QR1 <- compute_score(QR, score_pond = c(m7 = 2, q = 3, qs_residual_sa_on_sa = 5))
QR2 <- compute_score(QR, score_pond = c(m7 = 2, qs_residual_sa_on_sa = 5))

# Merge two quality report
try(rbind(QR1, QR2)) # Une erreur est renvoyée
rbind(QR1, QR2, check_formula = FALSE)
```

`recode_indicator_num` *Converting "values variables" into "modalities variables"*

Description

To transform variables from the values matrix into categorical variables that can be added into the modalities matrix.

Usage

```
recode_indicator_num(
  x,
  variable_name,
  breaks = c(0, 0.01, 0.05, 0.1, 1),
  labels = c("Good", "Uncertain", "Bad", "Severe"),
  ...
)
```

Arguments

x	a QR_matrix or mQR_matrix object.
variable_name	a vector of strings containing the names of the variables to convert.
breaks	see function cut .
labels	see function cut .
...	other parameters of the cut function.

Value

The function `recode_indicator_num()` returns the same object, enhanced with the chosen indicator. So if the input `x` is a `QR_matrix`, an object of class `QR_matrix` is returned. If the input `x` is a `mQR_matrix`, an object of class `mQR_matrix` is returned.

See Also

[Traduction française](#)

Other var `QR_matrix` manipulation: [QR_var_manipulation](#), [add_indicator\(\)](#)

sort	<i>QR_matrix and mQR_matrix sorting</i>
------	---

Description

To sort the quality reports on one or several variables

Usage

```
## S3 method for class 'QR_matrix'
sort(x, decreasing = FALSE, sort_variables = "score", ...)
```

```
## S3 method for class 'mQR_matrix'
sort(x, decreasing = FALSE, sort_variables = "score", ...)
```

Arguments

x	a QR_matrix or mQR_matrix object
decreasing	logical indicating whether the quality reports must be sorted in ascending or decreasing order. By default, the sorting is done in ascending order.
sort_variables	They must be present in the modalities table.
...	other parameters of the function order (unused for now)

Value

the input with sorted quality reports

See Also

[Traduction française](#)

Other QR_matrix functions: [export_xlsx\(\)](#), [export_xlsx.QR_matrix\(\)](#), [export_xlsx.mQR_matrix\(\)](#), [extract_QR\(\)](#), [rbind.QR_matrix\(\)](#), [weighted_score\(\)](#)

Examples

```
# Path of matrix demetra_m
demetra_path <- file.path(
  system.file("extdata", package = "JDCruncheR"),
  "WS/ws_ipi/Output/SAProcessing-1",
  "demetra_m.csv"
)

# Extract the quality report from the demetra_m file
QR <- extract_QR(demetra_path)

# Compute the score
QR <- compute_score(QR, n_contrib_score = 2)
print(QR$modalities$score)

# Sort the scores
QR <- sort(QR, sort_variables = "score") # Pour trier par ordre croissant sur le score
print(QR$modalities$score)
```

weighted_score

Weighted score calculation

Description

Function to weight a pre-calculated score

Usage

```
weighted_score(x, pond = 1)
```

Arguments

x	a QR_matrix or mQR_matrix object
pond	the weights to use. Can be an integer, a vector of integers, the name of one of the quality report variables or a list of weights for the mQR_matrix objects.

Value

the input with an additionnal weighted score

See Also

[Traduction française](#)

Other QR_matrix functions: [export_xlsx\(\)](#), [export_xlsx.QR_matrix\(\)](#), [export_xlsx.mQR_matrix\(\)](#), [extract_QR\(\)](#), [rbind.QR_matrix\(\)](#), [sort\(\)](#)

Examples

```
# Path of matrix demetra_m
demetra_path <- file.path(
  system.file("extdata", package = "JDCruncheR"),
  "WS/ws_ipi/Output/SAProcessing-1",
  "demetra_m.csv"
)

# Extract the quality report from the demetra_m file
QR <- extract_QR(demetra_path)

# Compute the score
QR <- compute_score(QR, n_contrib_score = 2)

# Weighted score
QR <- weighted_score(QR, 2)
print(QR)

# Extract the weighted score
QR$modalities$score_pond
```

Index

* QR_matrix functions

export_xlsx, 5
export_xlsx.mQR_matrix, 6
export_xlsx.QR_matrix, 7
extract_QR, 7
rbind.QR_matrix, 13
sort, 15
weighted_score, 16

* var QR_matrix manipulation

add_indicator, 2
QR_var_manipulation, 12
recode_indicator_num, 14

add_indicator, 2, 13, 15

compute_score, 3
create_param_file, 8
cruncher, 8
cruncher_and_param, 8
cut, 15

export_xlsx, 5, 6–8, 14, 16, 17
export_xlsx.mQR_matrix, 6, 6, 7, 8, 14, 16,
17
export_xlsx.QR_matrix, 5, 6, 7, 8, 14, 16, 17
extract_QR, 6, 7, 7, 14, 16, 17
extract_score, 9

is.mQR_matrix (QR_matrix), 11
is.QR_matrix (QR_matrix), 11

merge, 2
mQR_matrix, 2, 3, 5, 6, 9–12, 15, 16
mQR_matrix (QR_matrix), 11

order, 15

print.mQR_matrix (print.QR_matrix), 10
print.QR_matrix, 10

QR_matrix, 2, 3, 5, 7–9, 11, 11, 12–16

QR_var_manipulation, 3, 12, 15

rbind.QR_matrix, 6–8, 13, 16, 17
recode_indicator_num, 2, 3, 13, 14
remove_indicators
(QR_var_manipulation), 12
retain_indicators
(QR_var_manipulation), 12

sort, 6–8, 14, 15, 17

Traduction française, 3, 5–9, 11–17

weighted_score, 6–8, 14, 16, 16